

Aqueous acrylic polymer, to be used as an adhesion promoter for non or little absorbent surfaces before applying Luxury Concrete Microcement®.

RECOMMENDATIONS FOR USE

The support must be dry, clean, firm and free of fats or oils. It will have to dry a minimum of 30 minutes and not more than 24 hours before applying the first coat of Microcement.

Application temperature: between 12 and 30°C.

CONSUMPTION

Between 10 and 14 m² per liter, varying depending on the porosity of the support.

SPECIAL PRECAUTIONS

In case of contact with eyes, clean with plenty of water for 15 minutes. In case of skin contact wash with soap and water.

Do not ingest. If swallowed, do not induce vomiting and seek medical attention immediately.

Keep out of the reach of children.

It is recommended to comply with the following measures:

- Good ventilation
- Protective glasses
- Rubber gloves

Empty containers must be disposed of in accordance with current legal regulations. To avoid the product to dry or thicken close the lid after each use.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment. With the exception of the indications already specified, it is not needed to carry out any special recommendation concerning the applications of this product.

STORAGE CONDITIONS

The products of Luxury Concrete should be stored in their closed original packaging, sheltered from the weather at temperatures between 5°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of manufacturing, if stored correctly.

The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.



PROPERTIES

Adhesion promoter for supports with little or no absorption.

Application by roller or brush in one single coat.

Water based, non-flammable.

Free of plasticizers, solvents, ammonia and free of emulsifiers.

The product is supplied ready for use.

CLEANING OF THE TOOLS

The tools should be cleaned with water and soap immediately after using.

PACKAGING

Available in 5 litre plastic container

