

Concrete Finish WT Pool.

Concrete Finish WT Pool is a lithium salt based water-based sealer for Concrete Pool that creates a protective and consolidating film.



Technical data

Properties	Specification	Unit	Method
Features	Aqueous solution of Li salts		
Non-volatile content	14-16	%	UNE-EN ISO 3251:2020
Density	1,02±0,05	g/cm ³	UNE-EN ISO 2811-1
pH	10.5-11.5		UNE-EN ISO 19396-1
Touch drying time (23°C RH:50%)	30-60	min	
Drying time between layers	24	hours	
Performance	10-15	m ² /L	

CHEMICAL RESISTANCES: Immersion method UNE-EN 13529

Legend

- 5: No visible change.
- 4: Slight change, only visible with change of light.
- 3: Moderate visible mark
- 2: Significant marking without affecting surface structure.
- 1: Important mark, affects the surface structure.

The results obtained are based on an application of 2 layers of varnish 24 hours between layers and after 7 days of application. The contact with the chemical agent tested was 24 hours, one week and one month.

Product	Contact time 24 H	Contact time 1 week	Contact time 1 month
Water	5	5	5
Chlorinated water	5	5	5

Properties

- It offers high durability and improved chemical and wear resistance.
- Resistant to microcement alkalinity
- High adhesion
- Water-based, low VOC (volatile organic compounds), environmentally friendly product
- Easy application.

Presentation

It comes in 5-litre containers.

Application

Before application, be sure to thoroughly clean the surface. It will be necessary to allow at least 24 hours before applying the sealer to the microcement. Shake Concrete Finish WT Pool and apply by spraying at low pressure and spreading evenly by roller or brush to completely cover the substrate, avoiding areas of overspray. Allow each layer to dry for at least 24 hours before applying the next layer. Do not overcoat as this may cause incorrect curing and discolouration.

Avoid leaving traces. Allow to dry, do not add product before it is dry/consolidated. Wait at least 7 days after applying Concrete Finish WT Pool before filling the pool.

The ambient temperature should be between 5 - 30°C, without excessive wind.

The temperature of the substrate should be between 5 - 25°C .

Storage

It should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.

Special precautions

Concrete Finish WT Pool is alkaline and may cause eye and skin irritation. Avoid prolonged contact with skin and eyes and wear appropriate protective equipment during application. See product data sheet.

Cleaning of tools

The tools are washed with water immediately after use.