

Concrete Pro Wax.

Concrete Pro Wax is a maintenance wax for pavements of high resistance and metallic finishes. It provides high gloss and does not yellow.



Properties

- High gloss
- High resistance
- Metallic appearance
- Non-yellowing
- Easy to use

Consumption

By machine 20 - 40 mL/m²
By hand 30 - 50 mL/m²

Technical data

- Nature: Metallised emulsion based on acrylic polymers, PE waxes and additives
- Appearance: Opaque liquid
- Colour: White
- % solids: 23 ± 2
- pH: 9 ± 0,5
- Viscosity (Ford 4 cup): 13 ± 1s
- Density: 1,03 ± 0,01 g/mL
- Application temperature: Ambient temperature

Application

Use the product PURE, without dilution with water or any other solvent.

Apply two coats of Concrete Pro Wax on the surface of the microcement already sealed, cured and completely clean, using any of the cleaners Concrete Clean or Concrete Pro Clean.

It should be taken into account that the waxing treatment is not permanent, it is necessary to repeat the process from time to time, depending on the use of the surface.

Important: before waxing, wait at least two weeks after the application of the Concrete Finish WT, to ensure proper curing and to avoid damage.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.
In case of contact with skin wash with soap and water. Do not swallow. If swallowed do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with legal regulations.
To prevent the product from drying out or thickening, close the lid after each use.
This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.
This product does not contain any harmful substances that would require, under the current regulations, any additional labelling measures.
Keep out of reach of children.

Storage conditions

The product should be stored in its closed original packaging, protected from weather conditions at temperatures between 10°C and 30°C in a dry and well ventilated place, away from direct heat and sunlight. Shelf life is 1 year from the date of production, if stored in well-preserved conditions.

Packaging

It is available in bottles of 5 litres.

Cleaning of tools

Tools should be cleaned with water and soap immediately after use.