

Primacrete ABS.

Uses

As a primer based on acrylic copolymers, used as a bonding bridge for absorbent surfaces before applying microcement.

Properties

- Improves adhesion between absorbent substrates such as plasterboard or plaster and microcement.
- Easy to apply, ready-to-use product.
- Water-based product, low VOC (volatile organic compounds), environmentally friendly.

Technical information

PROPERTIES	SPECIFICATION	UNIT	METHOD
Nature	Acrylic emulsion		
pH	7-8		UNE-EN ISO 19396-1:2020
Density	1,02±0,05	g/cm ³	UNE-EN ISO 2811-1
Non-volatile content	10-12	%	UNE-EN ISO 3251:2020
Performance	8-12	m ² /L	
VOC:2024/42/IIA(h)(30) Max.VOCs	<5	g/L	
Drying time to touch	30	minutes	

Special precautions

It is essential to follow the instructions on the package label. For more information for further information, please refer to the safety data sheet of the product. Empty containers must be disposed of in accordance with current legislation.

Storage conditions

The product must be stored in its original closed container and protected from direct sunlight in the open air at temperatures between 10°C and 30°C, in a dry and well-ventilated place, in a dry and well-ventilated place ventilated, away from heat sources and direct sunlight. The shelf life is 1 year from date of manufacture, properly stored.



Application

The supports shall be clean and free of grease, oils, oxides, paint residues, etc and loose or poorly adhering parts. Apply to the surface by brush or roller. Cover the entire surface, taking care to apply a uniform film. The application temperature should be between 5 -30°C. Wait 1 hour approximately for the application of microcement.

Presentation

It is available in 1 and 5 L containers.

Cleaning of tools

The tools are washed with water immediately after use.