

Primacrete Finish.

Primacrete Finish is a water-based sealer to harden and homogenize microcements. It serves as an adhesion bridge between the microcement and the sealing varnish.



Properties

- Consolidates microcement coatings.
- Stable in humid environment.
- Resistant to the alkalinity of microcement.
- High adhesion.
- Easy to apply.

Consumption

- 2 coat: 0.12 l/m²

Application

As a primer for walls and floors:

Before applying Primacrete Finish it is essential to check that the substrate is dry and dust free. Depending on the climatic conditions and the ventilation of the working space, it is necessary to allow at least 24 hours to elapse before applying the primer on the microcement.

Apply by short haired microfibre roller in two coats, spaced 4 hours apart.

After applying Primacrete Finish, it is essential to protect the surface with at least two additional coats of one of our with at least two additional coats of our Concrete Finish WT varnishe to increase the chemical and abrasion resistance of the coating.

Technical data

- Water based emulsion
- Milky liquid
- Solids: 18 %.
- PH between 7 and 8.5
- Viscosity 10-11 s (Ford Cup 4)
- Density at 20°C: 1 ± 0,01 g/ml
- Application temperature from 5°C to 35°C (41°F TO 95°F)
- Touch dry 20 minutes

Special precautions

In case of contact with skin wash with soap and water.

Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.
- Empty containers should be disposed of in accordance with the legal regulations in force.

To prevent the product from drying out or thickening, close the lid after each use.

This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under current regulations, any additional labelling measures.

Keep out of reach of children.

For further information see product safety data sheet.

Packaging

Available in 5 litre containers.

Storage conditions

The product should be stored in its original closed packaging and protected from the weather at temperatures between 10°C and 30°C, in a dry and well-ventilated place, in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if properly stored.

Cleaning of tools

Tools should be washed with soap and water immediately after use.