

Primacrete Joint.

Primacrete Joint is a joint filler used to fill tile joints and smooth surfaces. It can be applied in interiors such as bathrooms or kitchens and also outdoors, due to its high resistance to water and humidity. Ready-to-use product to facilitate the application of Easycret ready-to-use microcements.



Technical data

- Colour: Cream white
- Aspect: Paste or putty
- Density: 1,80 g/cm³
- Codification (EN 16-566): G3 S2 V1 W2 A0 C0 R0
- Classification (NFT 36-005): Family IV-4b
- Drying to touch (23°C): 2 - 4 h
- Complete drying (23°C): 12 - 24 h
- Sanding/painting: After drying

Properties

- High adhesion on tiles and ceramics. Can be applied on: plaster, plasterboard, concrete, cellular concrete, bricks, stone, mortar, painted surfaces, etc.
- To adapt to the joint thickness it is available for: 0 - 2 mm, 2 - 5 mm, 5 - 10 mm.
- Resistant to water and ambient humidity.
- Ideal for ready-to-use microcement, Easycret.

Application

- Before applying Primacrete Joint, it is essential to check that the substrate is dry, free of dust, limescale and dirt.
- Depending on the environmental conditions and the ventilation of the workspace, it will be necessary to allow 12 - 24 hours to elapse before applying the microcement Luxury Concrete®.
- Do not apply at temperatures below 8°C or above 35°C, or at humidities of more than 80%.
- Do not apply on heated surfaces or in direct sunlight.
- Do not apply on substrates subject to permanent humidity.

Special precautions

Non-flammable product.
In case of contact with skin wash with soap and water. Never use solvents or thinners.
Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Rubber gloves.

Empty containers should be disposed of in accordance with legal regulations.
To prevent the product from drying out or thickening, close the lid after each use.
Keep out of reach of children.

Consumption

Consumption as smoothing:

- 1,1 kg/m²/mm aprox.

Applied on tile joints:

- 8 - 10 g/m²/mm aprox.

Characteristics

- Indoor/outdoor polyurethane resin and selected aggregates.
- Water based.
- Solids: 88 ± 2%

Preparation of the substrate

Stir contents before use.

Application material: spatula or trowel.

Packaging

Available in 1 and 3 Kg containers.

Storage conditions

The product should be stored in its original closed packaging and protected from the weather at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, properly stored.

Cleaning of tools

The tools are washed with water immediately after use.