

Primacrete PLUS.

Uses

As a primer based on acrylic copolymers, used as a bonding bridge between non-absorbent surfaces before applying microcement.

Properties

- Improves adhesion between non-absorbent substrates such as tiles and microcement.
- Easy to apply, ready-to-use product.
- Water-based product, low VOC (volatile organic compounds), environmentally friendly.



Application

The substrates must be clean and free of grease, oils, oxides, paint residues and loose or poorly adhering parts. Apply to the surface by brush or roller. Cover the entire surface, trying to apply a uniform film. The application temperature should be between 5 -30° C. Wait approximately 1 hour before applying the microcement.

Technical information

PROPERTIES	SPECIFICATION	UNIT	METHOD
Nature	Acrylic emulsion		
pH	8-9		UNE-EN ISO 19396-1:2020
Density	1,05±0,05	g/cm ³	UNE-EN ISO 2811-1
Non-volatile content	33-35	%	UNE-EN ISO 3251:2020
Performance	8-12	m ² /L	
VOC:2024/42/IIA(h)(30) Max.VOCs	<5	g/L	
Drying time to touch	30	minutes	

Cleaning of tools

The tools are washed with water immediately after use.

Presentation

It comes in 1 and 5L containers.

Special precautions

It is essential to follow the instructions on the label of the container. For further information, please refer to the product safety data sheet. Empty containers must be disposed of in accordance with current legislation.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C, in a dry and well ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if stored properly.